

Next Generation R-Series Oil-Flooded Rotary Screw Air Compressors

45-75 kW (60-100 hp)

Ingersoll Rand works to keep you ahead of your competition with Next Generation R-Series air compressors that lower total cost of ownership through high-quality components, industry-leading energy efficiency and global expertise.




World-class performance

- Designed for significantly improving efficiency** with state-of-the-art airends, IE3/NEMA Premium® high-efficiency motor, a free-floating cooling system and optional Energy Recovery System (ERS) significantly improve efficiency
- V-Shield™ technology** provides a totally integrated, leak-free design featuring PTFE stainless steel braided oil hoses and O-ring face seals
- Xe-Series controller** delivers increased control functionality through an intuitive user interface as well as remote access with any common, current web browser
- Progressive Adaptive Control (PAC™)** monitors key operating parameters and continuously adapts to prevent unexpected downtime
- Enhanced serviceability** ensures increased uptime with features such as two-stage filtration, easy maintenance and Ingersoll Rand extended life, premium grade coolant
- Hinged-door service access with integrated handles** provides quick, easy access to all user-maintainable components
- Optional Total Air System (TAS)** provides clean, dry air in a single package that minimizes installation costs, reduces footprint and improves ISO air quality



Standard features include:	Optional features include:
Premium performance airend	Total Air System (TAS) package with integrated air dryer
Energy saving, intuitive Xe-90M Series controller with remote access	XE 145M Controller with a 145mm screen
Air-cooled free-floating cooling system with moisture separator	Low ambient temperature protection as low as -23°C (-10°F)
PAC™ protection adjusts operating parameters in response to compressor operation	Outdoor modification/rain protection
V-Shield™ stainless steel piping, vibration isolation, PTFE hoses, leak-free connections	Premium high dust filtration
Noise attenuation enclosure with hinged removable doors for easy service access	Water-cooled system
Packaged pre-filtration	Ultra EL lubricant (extended 16,000-hour life)
Long-life Ultra Coolant with 8,000-hour life	Ultra FG lubricant (food grade)
Long-life filtration and separation elements	Power outage automatic restart option (PORO)
Control panel protection	Comprehensive service and coverage plans
Star-delta reduced voltage starter	Flow control inlet modulation
Premium TEFC motor	Phase monitor protection
Package rated for 46°C (115°F) ambient operation	High ambient rating up to 55°C (131°F)
	Containment base
	Soft Starter



Standard 50 Hz Performance

Model	Max pressure barg	Nominal power kW	Capacity (FAD)* m ³ /min	Dimensions (L x W x H) mm	Weight (Air-cooled) kg	Weight (Water-cooled) kg
RS45i	7.5	45	8.9	2,433 x 1,250 x 2,032	1,841	1746
RS45i	8.5	45	8.3		1,841	1746
RS45i	10.0	45	7.7		1,841	1746
RS45i	14.0	45	5.9		1,841	1746
RS55i	7.5	55	11.2		1,936	1841
RS55i	8.5	55	10.4		1,936	1841
RS55i	10.0	55	9.3		1,936	1841
RS55i	14.0	55	7.4		1,936	1841
RS75i	7.5	75	14.5		1,962	1867
RS75i	8.5	75	13.9		1,962	1867
RS75i	10.0	75	13.0		1,962	1867
RS75i	14.0	75	10.7		1,962	1867

Total Air System (TAS) 50 Hz Performance

Model	Max pressure barg	Nominal power kW	Capacity (FAD)* m ³ /min	Dimensions (L x W x H) mm	Weight (Air-cooled) kg	Weight (Water-cooled) kg
RS45i	7.0	45	8.9	2,433 x 1,250 x 2,032	1,994	1899
RS45i	8.0	45	8.3		1,994	1899
RS45i	9.5	45	7.7		1,994	1899
RS45i	13.5	45	5.9		1,994	1899
RS55i	7.0	55	11.2		2,089	1994
RS55i	8.0	55	10.4		2,089	1994
RS55i	9.5	55	9.3		2,089	1994
RS55i	13.5	55	7.4		2,089	1994
RS75i	7.0	75	14.5		2,115	2020
RS75i	8.0	75	13.9		2,115	2020
RS75i	9.5	75	13.0		2,115	2020
RS75i	13.5	75	10.7		2,115	2020



IngersollRandProducts.com

Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.



Ingersoll Rand, IR and the IR logo are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates. All other trademarks are the property of their respective owners. Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialised equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Any designs, diagrams, pictures, photographs and specifications contained within this document are for representative purposes only and may include optional scope and/or functionality and are subject to change without notice or obligation.